

X-ray machine | Screening machine

Brand : Supper Strong

Model : CQ-5030

Price Tk. 8,75000.00



Detect objects: parcels, mail, small bags, suitcase, bag and other small items

Application areas: tax, courts, detention centers, prisons, tourist attractions, sports centers, post offices, shopping malls, hotels, footwear, clothing, toys, luggage and other places

Most real technical advantages:

* One-touch off: simply rotate the shutdown at the keys, automatic safety shutdown equipment, more humane

* Emergency stop hierarchical control system: emergency stop button is pressed, only the drive and power outages ray source part, safer

Dongguan Chao Qiang Electronic Technology Co., Ltd. Tel: +86-769-23050998 / 22551783 , Fax: +86-769-27234620 Website : www.hecq88.com

Local Distributor: ZM International, House#8/5, 2nd Floor, Road#1, Shamoly, Dhaka- 1207 Phone: +88 02 9142448, 9142556, Cell: +88 01920 953852, 01920 098535 E-mail: info@zmintl.com www.zmintl.com

- * Ultra-clear images: high-density core components imported modules, higher resolution, up to international standards, clearer
- * Waterproof function: Channel special treatment, a small amount of liquid passengers scattered no effect, more confidence
- * Jiro Mirror Features: Unique Mouse Magnifier, any local details zoom, more accurate
- * Promise day eye magnification: 128 consecutive Promise mouse zoom function, more continuous
- * Magic button: instead of the traditional keyboard, when the mouse into the soft buttons, intelligent recognition software control, more intelligent
- * Roaring days of dog Electronic Nose: audible alarm signal is issued when certain conditions are met, to assist in identifying the role of particular have
- * Fault self-diagnosis: faulty automatic judgment, and gives tips for easy maintenance
- * Black box :(optional module)

Basic technical parameters:

Dimensions: 1650 (L) x722 (width) X1150 (H) mm

Channel Dimensions: 500 (W) X300 (H) mm

Transmission speed: 0.22 m / sec.

Drag Weight: 150 kg

Resolution: 0.101mm diameter wire

Penetration: 10mm steel

Film Safety: ISO1600 film for safety

Ray beam direction: Bottom-illuminated

Tube current: 0.4-1.2mA (adjustable)

Tube voltage: 80KV (adjustable)

Leakage dose: <0.05uGy / h

Beam divergence angle: 60 °

Cooling / duty cycle: Sealed oil-cooled / 100

Working environment: -20 ° C ~ 60 ° C / 20% ~ 95% (non-condensing)

Noise: ≤55dB

Operating voltage: 220VAC (± 10%) 50 ± 3HZ

Power: 0.5KVA (0.5 kWh per hour)

Image processing:

Array detector: L-type photodiode detector single energy

Display: 19 inches high-resolution LCD

Pseudo-color: color image display 24 displays, 12bit depth

Edge Enhancement: an object more clearly outline the edges

Super image enhancement Figure: Like sharper details

High wear show: to improve the image contrast of the bright areas, so as to penetrate the area more clearly

Low wear show: to improve the image contrast of dark areas, so as to penetrate the area more clearly

Brightening / dimming: increase the brightness of the image / decrease the brightness of dark images

Pull back / front pull: Can the current 30 images, before pulling back and handling

Image restoration: image display restored to its original state

Image storage: Continuous save 500,000 images, and can handle